

Specifications							
Parameter	NetEngine 8000 X8	NetEngine 8000 X4	NetEngine 8000 M14	NetEngine 8000 M8	NetEngine 8000 M6	NetEngine 8000 M1A	NetEngine 8000 F1A
Switching Capacity	83.78 Tbit/s	41.89 Tbit/s	4 Tbit/s	2.4 Tbit/s	320 Gbit/s	352 Gbit/s	2.4 Tbit/s
Forwarding Performance	14,496 Mpps	7248 Mpps	906 Mpps	453 Mpps	72 Mpps	72 Mpps	453 Mpps
Max. Capacity of a Board	4 Tbit/s	4 Tbit/s	200 Gbit/s	200 Gbit/s	50 Gbit/s	Fixed-configuration router does not support flexible cards	Fixed-configuration router does not support flexible cards
Capacity Density (G/U)	2025	1633	400	400	80	176	1200
IPU	2, 1:1	2, 1:1	2, 1:1	2, 1:1	2, 1:1	Fixed-configuration router does not support flexible cards	Fixed-configuration router does not support flexible cards
SFU	8, 7+1	8, 7+1	2, 1:1 (integrated)	2, 1:1 (integrated)	2, 1:1 (integrated)	Fixed-configuration router does not support flexible cards	Fixed-configuration router does not support flexible cards
Processing Board/Subcard	8	4	14(DC) 10(AC)	8(DC) 6(AC)	6(DC) 4(AC)	Fixed-configuration router does not support flexible cards	Fixed-configuration router does not support flexible cards
Power Supply Module	Max 10, N+1	Max 6, N+1	2, 1+1 (DC) 4, 2+2 (AC)	2, 1+1	2, 1+1	2, 1+1 (DC)	2, 1+1
Fan Module	12, 11+1	6, 5+1	4, 3+1	2, 1+1	2, 1+1	3 (integrated)	4, 3+1
Dimensions (H x W x D)	702.3 x 442 x 861.4 mm (15.8 U)	435.6 x 442 x 861.4 mm (9.8 U)	222 x 442 x 220 mm (5 U)	132.6 x 442 x 220 mm (3 U)	88.9 x 442 x 220 mm (2 U)	44.45 x 442 x 220 mm (1 U)	43.6 x 442 x 420 mm (1 U)
Typical Power Consumption	11,017 W	5913 W	1270 W	485 W	220 W	75 W	350 W
Weight (With Full Configuration)	296.6 kg	186.2 kg	27.4 kg	16.5 kg	3.52 kg	3.4 kg	7.25 kg